# iline 4

( +44 (0) 1279 450882

() WWW.RIDI-GROUP.CO.UK

- SALES@RIDI.CO.UK

#### Luminaire type

Product reference: Article Number: Product type: Mounting type: Applications:

IL4-WS-1132-830M-DADI-MP-FG 97-IL400003 Pendant Pendant Office, General and Retail

## **Specification text**

Pendant luminaire from the iline 4 family. Symmetrical, Wide lighting distribution, UGR 19. Light output of 3113lm with an efficacy of 111lm/W. Light source colour temperature 3000KK and CRI 85. Complete with DALI control gear. Nominal dimensions L1132 x W40 x H62mm. Finished in Grey.

> 3113 lm 111 lm/W 28.1W DALI 1-100% Yes 3000K K < 3 85



## Lighting performance

Output lumens:
Efficacy:
Rated power:
Control gear:
Dimming range:
DC Suitable:
Colour temperature:
MacAdams
CRI:
Radiation pattern:
Beam angle:
Unified glare rating (U.G.R):


#### **Physical details**

Finish:	
Length:	
Width:	
Height:	
IP Rating:	



Symmetrical Wide 19







RIDI

The details provided in this data sheet were prepared with due care but are still subject to error. We retain the right to make formal, technical and pricing changes. © 21/03/25 RIDI Lighting Ltd, Units 8 & 9 The Marshgate Centre, Harlow Business Park, Parkway, Harlow, Essex, CM19 5QP.