iline 4

(+44 (0) 1279 450882

() WWW.RIDI-GROUP.CO.UK

- SALES@RIDI.CO.UK

Luminaire type

Product reference: Article Number: Product type: Mounting type: Applications:

IL4-WS-1132-840M-DADI-MP-FGE 97-IL400009E Pendant Pendant Office, General and Retail

Specification text

Pendant luminaire from the iline 4 family. Symmetrical, Wide lighting distribution, UGR 19. Light output of 3209lm with an efficacy of 114lm/W. Light source colour temperature 4000KK and CRI 85. Complete with DALI control gear and manual test 3hr emergency. Nominal dimensions L1132 \times W40 \times H62mm. Finished in Grey.

> 3209 lm 114 lm/W 28.1W DALI 1-100% Yes 4000K K < 3 85

Symmetrical Wide 19



Lighting performance


Output lumens:
Efficacy:
Rated power:
Control gear:
Dimming range:
DC Suitable:
Colour temperature:
MacAdams
CRI:
Radiation pattern:
Beam angle:
Unified glare rating (U.G.R):

Physical details

Finish:	
Length:	
Width:	
Height:	
IP Rating:	







lightworks

RIDI

The details provided in this data sheet were prepared with due care but are still subject to error. We retain the right to make formal, technical and pricing changes. © 21/03/25 RIDI Lighting Ltd, Units 8 & 9 The Marshgate Centre, Harlow Business Park, Parkway, Harlow, Essex, CM19 5QP.