iline 4

(+44 (0) 1279 450882

() WWW.RIDI-GROUP.CO.UK

- SALES@RIDI.CO.UK

Luminaire type

Product reference: Article Number: Product type: Mounting type: Applications:

IL4-WS-1132-840M-DADI-OP-FWES 97-IL400016ES Pendant Pendant Office, General and Retail

Specification text

Pendant luminaire from the iline 4 family. Symmetrical, Wide lighting distribution, UGR 22. Light output of 3548lm with an efficacy of 126lm/W. Light source colour temperature 4000KK and CRI 85. Complete with DALI control gear and self test 3hr emergency. Nominal dimensions L1132 x W40 x H62mm. Finished in White.



Lighting performance


Output lumens:	3548 Im
Efficacy:	126 lm/W
Rated power:	28.1 W
Control gear:	DALI
Dimming range:	1-100%
DC Suitable:	Yes
Colour temperature:	4000K K
MacAdams	< 3
CRI:	85
Radiation pattern:	Symmetrical
Beam angle:	Wide
Unified glare rating (U.G.R):	22

Physical details

Finish:	
Length:	
Width:	
Height:	
IP Rating:	

White 1132 mm 40 mm 62 mm IP20





lightworks

RIDI

The details provided in this data sheet were prepared with due care but are still subject to error. We retain the right to make formal, technical and pricing changes. © 21/03/25 RIDI Lighting Ltd, Units 8 & 9 The Marshgate Centre, Harlow Business Park, Parkway, Harlow, Essex, CM19 5QP.