

## Luminaire type

|                    |                            |
|--------------------|----------------------------|
| Product reference: | IL4-S-1132-840M-DAD-MP-FBE |
| Article Number:    | 97-IL400044E               |
| Product type:      | Surface Mount              |
| Mounting type:     | Surface                    |
| Applications:      | Office, General and Retail |

## Specification text

Surface Mount luminaire from the iline 4 family. Symmetrical, Wide lighting distribution, UGR 19. Light output of 2119lm with an efficacy of 109lm/W. Light source colour temperature 4000KK and CRI 85. Complete with DALI control gear and manual test 3hr emergency. Nominal dimensions L1132 x W40 x H62mm. Finished in Black.



## Lighting performance

|                               |             |
|-------------------------------|-------------|
| Output lumens:                | 2119 lm     |
| Efficacy:                     | 109 lm/W    |
| Rated power:                  | 19.5 W      |
| Control gear:                 | DALI        |
| Dimming range:                | 1-100%      |
| DC Suitable:                  | Yes         |
| Colour temperature:           | 4000K K     |
| MacAdams                      | < 3         |
| CRI:                          | 85          |
| Radiation pattern:            | Symmetrical |
| Beam angle:                   | Wide        |
| Unified glare rating (U.G.R): | 19          |



## Physical details

|            |         |
|------------|---------|
| Finish:    | Black   |
| Length:    | 1132 mm |
| Width:     | 40 mm   |
| Height:    | 62 mm   |
| IP Rating: | IP20    |

