# iline 4

( +44 (0) 1279 450882

() WWW.RIDI-GROUP.CO.UK

- SALES@RIDI.CO.UK

#### Luminaire type

Product reference:
Article Number:
Product type:
Mounting type:
Applications:

IL4-S-1132-840M-DAD-OP-FBE 97-IL400053E Surface Mount Surface Office, General and Retail

## **Specification text**

Surface Mount luminaire from the iline 4 family. Symmetrical, Wide lighting distribution, UGR 22. Light output of 2458Im with an efficacy of 126Im/W. Light source colour temperature 4000KK and CRI 85. Complete with DALI control gear and manual test 3hr emergency. Nominal dimensions L1132 x W40 x H62mm. Finished in Black.

> 2458 lm 126 lm/W 19.5 W DALI 1-100% Yes 4000K K < 3 85

Symmetrical Wide 22



## Lighting performance


Output lumens:
Efficacy:
Rated power:
Control gear:
Dimming range:
DC Suitable:
Colour temperature:
MacAdams
CRI:
Radiation pattern:
Beam angle:
Unified glare rating (U.G.R):

#### **Physical details**

Finish:	
Length:	
Width:	
Height:	
IP Rating:	







lightworks

RIDI

The details provided in this data sheet were prepared with due care but are still subject to error. We retain the right to make formal, technical and pricing changes. © 21/03/25 RIDI Lighting Ltd, Units 8 & 9 The Marshgate Centre, Harlow Business Park, Parkway, Harlow, Essex, CM19 5QP.