iline 4

(+44 (0) 1279 450882

() WWW.RIDI-GROUP.CO.UK

- SALES@RIDI.CO.UK

Luminaire type

Product reference:	IL6-R-1137-830M-DAD-MP-FWE
Article Number:	97-IL400120E
	Recessed
	Recessed
5 51	Office, General and Retail

Specification text

Recessed luminaire from the iline 4 family. Symmetrical, Wide lighting distribution, UGR 19. Light output of 2055Im with an efficacy of 105Im/W. Light source colour temperature 3000KK and CRI 85. Complete with DALI control gear and manual test 3hr emergency. Nominal dimensions L1137 $x\,W54\,x$ H85mm. Finished in White.

> 2055 lm 105 lm/W 19.5 W DALI 1-100% Yes 3000K K < 3 85

Symmetrical Wide 19

Lighting performance

Output lumens:	
Efficacy:	
Rated power:	
Control gear:	
Dimming range:	
DC Suitable:	
Colour temperature:	
MacAdams	
CRI:	
Radiation pattern:	
Beam angle:	
Unified glare rating (U.G.R):	


Physical details

Finish:	
Length:	
Width:	
Height:	
IP Rating:	

White 1137 mm 54 mm 85 mm IP20







lightworks

RIDI

The details provided in this data sheet were prepared with due care but are still subject to error. We retain the right to make formal, technical and pricing changes. © 21/03/25 RIDI Lighting Ltd, Units 8 & 9 The Marshgate Centre, Harlow Business Park, Parkway, Harlow, Essex, CM19 5QP.