iline 4

(+44 (0) 1279 450882

() WWW.RIDI-GROUP.CO.UK

- SALES@RIDI.CO.UK

Luminaire type

Product reference:			
Article Number:			
Product type:			
Mounting type:			
Applications:			


IL6-R-1137-840M-DAD-OP-FGE 97-IL400131E Recessed Recessed Office, General and Retail

Specification text

Recessed luminaire from the iline 4 family. Symmetrical, Wide lighting distribution, UGR 22. Light output of 2458lm with an efficacy of 126lm/W. Light source colour temperature 4000KK and CRI 85. Complete with DALI control gear and manual test 3hr emergency. Nominal dimensions L1137 $x\,W54\,x$ H85mm. Finished in Grey.

> 2458 lm 126 lm/W 19.5 W DALI 1-100% Yes 4000K K < 3 85

Symmetrical Wide 22



Lighting performance

Output lumens:
Efficacy:
Rated power:
Control gear:
Dimming range:
DC Suitable:
Colour temperature:
MacAdams
CRI:
Radiation pattern:
Beam angle:
Unified glare rating (U.G.R):

Physical details


Finish:		
Length:		
Width:		
Height:		
IP Rating:		



Grey

1137 mm 54 mm 85 mm





lightworks

RIDI

The details provided in this data sheet were prepared with due care but are still subject to error. We retain the right to make formal, technical and pricing changes. © 21/03/25 RIDI Lighting Ltd, Units 8 & 9 The Marshgate Centre, Harlow Business Park, Parkway, Harlow, Essex, CM19 5QP.