# iline 4

( +44 (0) 1279 450882

() WWW.RIDI-GROUP.CO.UK

- SALES@RIDI.CO.UK

### Luminaire type

Product reference: Article Number: Product type: Mounting type: Applications:

IL4-WS-1482-840M-DADI-MP-FWES 97-IL400207ES Pendant Pendant Office, General and Retail

#### **Specification text**

Pendant luminaire from the iline 4 family. Symmetrical, Wide lighting distribution, UGR 19. Light output of 4201lm with an efficacy of 114lm/W. Light source colour temperature 4000KK and CRI 85. Complete with DALI control gear and self test 3hr emergency. Nominal dimensions L1482 x W40 x H62mm. Finished in White.

> 4201 lm 114 lm/W 36.9 W DALI 1-100% Yes 4000K K < 3 85



#### Lighting performance

| Output lumens:                |
|-------------------------------|
| Efficacy:                     |
| Rated power:                  |
| Control gear:                 |
| Dimming range:                |
| DC Suitable:                  |
| Colour temperature:           |
| MacAdams                      |
| CRI:                          |
| Radiation pattern:            |
| Beam angle:                   |
| Unified glare rating (U.G.R): |


#### **Physical details**

| Finish:    |
|------------|
| Length:    |
| Width:     |
| Height:    |
| IP Rating: |
|            |

## White 1482 mm 40 mm 62 mm IP20

Symmetrical Wide 19





The details provided in this data sheet were prepared with due care but are still subject to error. We retain the right to make formal, technical and pricing changes. © 21/03/25 RIDI Lighting Ltd, Units 8 & 9 The Marshgate Centre, Harlow Business Park, Parkway, Harlow, Essex, CM19 5QP.



lightworks