# iline 4

( +44 (0) 1279 450882

() WWW.RIDI-GROUP.CO.UK

- SALES@RIDI.CO.UK

#### Luminaire type


Product reference: Article Number: Product type: Mounting type: Applications:

IL4-WS-1482-830M-DAD-MP-FG 97-IL400221 Pendant Pendant Office, General and Retail

### **Specification text**

Pendant luminaire from the iline 4 family. Symmetrical, Wide lighting distribution, UGR 19. Light output of 2691lm with an efficacy of 105lm/W. Light source colour temperature 3000KK and CRI 85. Complete with DALI control gear. Nominal dimensions L1482 x W40 x H62mm. Finished in Grey.

> 2691 lm 105 lm/W 25.7 W DALI 1-100% Yes 3000K K < 3 85



## Lighting performance

| Output lumens:                |
|-------------------------------|
| Efficacy:                     |
| Rated power:                  |
| Control gear:                 |
| Dimming range:                |
| DC Suitable:                  |
| Colour temperature:           |
| MacAdams                      |
| CRI:                          |
| Radiation pattern:            |
| Beam angle:                   |
| Unified glare rating (U.G.R): |


#### **Physical details**

| Finish:    |
|------------|
| Length:    |
| Width:     |
| Height:    |
| IP Rating: |
|            |

Grey 1482 mm 40 mm 62 mm IP20

Symmetrical Wide 19





# lightworks

RIDI

The details provided in this data sheet were prepared with due care but are still subject to error. We retain the right to make formal, technical and pricing changes. © 21/03/25 RIDI Lighting Ltd, Units 8 & 9 The Marshgate Centre, Harlow Business Park, Parkway, Harlow, Essex, CM19 5QP.