

Luminaire type

| | |
|--------------------|----------------------------|
| Product reference: | IL4-WS-1482-830M-DAD-OP-FW |
| Article Number: | 97-IL400228 |
| Product type: | Pendant |
| Mounting type: | Pendant |
| Applications: | Office, General and Retail |

Specification text

Pendant luminaire from the iline 4 family. Symmetrical, Wide lighting distribution, UGR 22. Light output of 3121lm with an efficacy of 122lm/W. Light source colour temperature 3000KK and CRI 85. Complete with DALI control gear. Nominal dimensions L1482 x W40 x H62mm. Finished in White.



Lighting performance

| | |
|-------------------------------|-------------|
| Output lumens: | 3121 lm |
| Efficacy: | 122 lm/W |
| Rated power: | 25.7 W |
| Control gear: | DALI |
| Dimming range: | 1-100% |
| DC Suitable: | Yes |
| Colour temperature: | 3000K K |
| MacAdams | < 3 |
| CRI: | 85 |
| Radiation pattern: | Symmetrical |
| Beam angle: | Wide |
| Unified glare rating (U.G.R): | 22 |



Physical details

| | |
|------------|---------|
| Finish: | White |
| Length: | 1482 mm |
| Width: | 40 mm |
| Height: | 62 mm |
| IP Rating: | IP20 |

