# iline 4

( +44 (0) 1279 450882

() WWW.RIDI-GROUP.CO.UK

- SALES@RIDI.CO.UK

#### Luminaire type

Product reference:
Article Number:
Product type:
Mounting type:
Applications:

IL4-S-1482-830M-DAD-MP-FGED 97-IL400239ED Surface Mount Surface Office, General and Retail

### **Specification text**

Surface Mount luminaire from the iline 4 family. Symmetrical, Wide lighting distribution, UGR 19. Light output of 2691lm with an efficacy of 105lm/W. Light source colour temperature 3000KK and CRI 85. Complete with DALI control gear and DALI test 3hr emergency. Nominal dimensions L1482 x W40 x H62mm. Finished in Grey.

> 2691 lm 105 lm/W 25.7 W DALI 1-100% Yes 3000K K < 3 85

Symmetrical Wide 19



#### Lighting performance


Output lumens:
Efficacy:
Rated power:
1
Control gear:
Dimming range:
DC Suitable:
Colour temperature:
MacAdams
CRI:
Radiation pattern:
Beam angle:
Unified glare rating (U.G.R):

#### **Physical details**

Finish:	
Length:	
Width:	
Height:	
IP Rating:	







## lightworks

RIDI

The details provided in this data sheet were prepared with due care but are still subject to error. We retain the right to make formal, technical and pricing changes. © 21/03/25 RIDI Lighting Ltd, Units 8 & 9 The Marshgate Centre, Harlow Business Park, Parkway, Harlow, Essex, CM19 5QP.