iline 4

(+44 (0) 1279 450882

() WWW.RIDI-GROUP.CO.UK

RIDI

- SALES@RIDI.CO.UK

Luminaire type

Product reference:	IL6-R-1487-840M-DAD-MP-FWES
Article Number:	97-IL400323ES
Product type:	Recessed
Mounting type:	Recessed
Applications:	Office, General and Retail

Specification text

Recessed luminaire from the iline 4 family. Symmetrical, Wide lighting distribution, UGR 19. Light output of 2774lm with an efficacy of 108lm/W. Light source colour temperature 4000KK and CRI 85. Complete with DALI control gear and self test 3hr emergency. Nominal dimensions L1487 x W54 x H85mm. Finished in White.

Lighting performance


Output lumens:	2774 lm
Efficacy:	108 lm/W
Rated power:	25.7 W
Control gear:	DALI
Dimming range:	1-100%
DC Suitable:	Yes
Colour temperature:	4000K K
MacAdams	< 3
CRI:	85
Radiation pattern:	Symmetrical
Beam angle:	Wide
Unified glare rating (U.G.R):	19

Physical details

Finish:	
Length:	
Width:	
Height:	
IP Rating:	

White 1487 mm 54 mm 85 mm IP20







The details provided in this data sheet were prepared with due care but are still subject to error. We retain the right to make formal, technical and pricing changes. © 21/03/25 RIDI Lighting Ltd, Units 8 & 9 The Marshgate Centre, Harlow Business Park, Parkway, Harlow, Essex, CM19 5QP.