iline 4

(+44 (0) 1279 450882

() WWW.RIDI-GROUP.CO.UK

- SALES@RIDI.CO.UK

Luminaire type


Product reference:
Article Number:
Product type:
Mounting type:
Applications:

IL6-R-1487-840M-DAD-OP-FB 97-IL400330 Recessed Recessed Office, General and Retail

Specification text

Recessed luminaire from the iline 4 family. Symmetrical, Wide lighting distribution, UGR 22. Light output of 3218Im with an efficacy of 125Im/W. Light source colour temperature 4000KK and CRI 85. Complete with DALI control gear. Nominal dimensions L1487 x W54 x H85mm. Finished in Black.

> 3218 lm 125 lm/W 25.7 W DALI 1-100% Yes 4000K K < 3 85



Lighting performance

Output lumens:
Efficacy:
Rated power:
Control gear:
Dimming range:
DC Suitable:
Colour temperature:
MacAdams
CRI:
Radiation pattern:
Beam angle:
Unified glare rating (U.G.R):


Physical details

Finish:		
Length:		
Width:		
Height:		
IP Rating:		

Black 1487 mm 54 mm 85 mm IP20

Symmetrical Wide 22





lightworks

RIDI

The details provided in this data sheet were prepared with due care but are still subject to error. We retain the right to make formal, technical and pricing changes. © 21/03/25 RIDI Lighting Ltd, Units 8 & 9 The Marshgate Centre, Harlow Business Park, Parkway, Harlow, Essex, CM19 5QP.