iline 4

(+44 (0) 1279 450882

() WWW.RIDI-GROUP.CO.UK

- SALES@RIDI.CO.UK

Luminaire type

Product reference: Article Number: Product type: Mounting type: Applications:

IL4-WS-1972-830M-DADI-MP-FB 97-IL400402 Pendant Pendant Office, General and Retail

Specification text

Pendant luminaire from the iline 4 family. Symmetrical, Wide lighting distribution, UGR 19. Light output of 5442lm with an efficacy of 110lm/W. Light source colour temperature 3000KK and CRI 85. Complete with DALI control gear. Nominal dimensions L1972 x W40 x H62mm. Finished in Black.

> 5442 lm 110 lm/W 49.1W DALI 1-100% Yes 3000K K < 3 85



Lighting performance

Output lumens:
Efficacy:
Rated power:
Control gear:
Dimming range:
DC Suitable:
Colour temperature:
MacAdams
CRI:
Radiation pattern:
Beam angle:
Unified glare rating (U.G.R):


Physical details

Finish:
Length:
Width:
Height:
IP Rating:

Black 1972 mm 40 mm 62 mm IP20

Symmetrical Wide 19





The details provided in this data sheet were prepared with due care but are still subject to error. We retain the right to make formal, technical and pricing changes. © 21/03/25 RIDI Lighting Ltd, Units 8 & 9 The Marshgate Centre, Harlow Business Park, Parkway, Harlow, Essex, CM19 5QP.

