# iline 4

- ( +44 (0) 1279 450882
- () WWW.RIDI-GROUP.CO.UK

- SALES@RIDI.CO.UK

#### Luminaire type

Product reference: Article Number: Product type: Mounting type: Applications:

IL4-WS-1972-830M-DADI-MP-FBE 97-IL400402E Pendant Pendant Office, General and Retail

## **Specification text**

Pendant luminaire from the iline 4 family. Symmetrical, Wide lighting distribution, UGR 19. Light output of 5442Im with an efficacy of 110Im/W. Light source colour temperature 3000KK and CRI 85. Complete with DALI control gear and manual test 3hr emergency. Nominal dimensions L1972  $\times$  W40  $\times$  H62mm. Finished in Black.

> 5442 lm 110 lm/W 49.1W DALI 1-100% Yes 3000K K < 3 85



## Lighting performance

Output lumens:
Efficacy:
Rated power:
Control gear:
Dimming range:
DC Suitable:
Colour temperature:
MacAdams
CRI:
Radiation pattern:
Beam angle:
Unified glare rating (U.G.R):


#### **Physical details**

Finish:
Length:
Width:
Height:
IP Rating:

## Black 1972 mm 40 mm 62 mm IP20

Symmetrical Wide 19





lightworks

RIDI

The details provided in this data sheet were prepared with due care but are still subject to error. We retain the right to make formal, technical and pricing changes. © 21/03/25 RIDI Lighting Ltd, Units 8 & 9 The Marshgate Centre, Harlow Business Park, Parkway, Harlow, Essex, CM19 5QP.