iline 5

+44 (0) 1279 450882

WWW.RIDI-GROUP.CO.UK

SALES@RIDI.CO.UK

Luminaire type

Product reference: Article Number: Product type: Mounting type: Applications: IL5-WS-1990-840M-DADI-MP-FWES 97-IL400407ES Pendant Pendant Office, General and Retail

Specification text

Pendant luminaire from the iline 5 family. Symmetrical, Wide lighting distribution, UGR <19. Light output of 10593Im with an efficacy of 117Im/W. Light source colour temperature 4000KK and CRI 85. Complete with DALI control gear. Nominal dimensions L1990 x W49 x H85mm. Finished in White.

10593 lm 117 lm/W 90.8 W DALI 1-100% Yes 4000K K < 3 85

Symmetrical Wide <19




Lighting performance


Output lumens:
Efficacy:
Rated power:
Control gear:
Dimming range:
DC Suitable:
Colour temperature:
MacAdams
CRI:
Radiation pattern:
Beam angle:
Unified glare rating (U.G.R):

Physical details

Finish:
Length:
Width:
Height:
IP Rating:

White 1990 mm 49 mm 85 mm IP20





lightworks

RIDI

The details provided in this data sheet were prepared with due care but are still subject to error. We retain the right to make formal, technical and pricing changes. © 21/03/25 RIDI Lighting Ltd, Units 8 & 9 The Marshgate Centre, Harlow Business Park, Parkway, Harlow, Essex, CM19 5QP.