iline 5

+44(0)1279450882

WWW.RIDI-GROUP.CO.UK

SALES@RIDI.CO.UK

Luminaire type

Product reference: Article Number: Product type: Mounting type: Applications:

IL5-WS-1990-840M-DADI-MP-FG 97-IL400409 Pendant Pendant Office, General and Retail

Specification text

Pendant luminaire from the iline 5 family. Symmetrical, Wide lighting distribution, UGR <19. Light output of 105931m with an efficacy of 1171m/W. Light source colour temperature 4000KK and CRI 85. Complete with DALI control gear. Nominal dimensions L1990 x W49 x H85mm. Finished in Grey.

> 10593 lm 117 lm/W 90.8 W DALI 1-100% Yes 4000K K < 3 85

Symmetrical Wide <19




Lighting performance


| Output lumens: |
|-------------------------------|
| Efficacy: |
| Rated power: |
| Control gear: |
| Dimming range: |
| DC Suitable: |
| Colour temperature: |
| MacAdams |
| CRI: |
| Radiation pattern: |
| Beam angle: |
| Unified glare rating (U.G.R): |

Physical details

| Finish: |
|------------|
| Length: |
| Width: |
| Height: |
| IP Rating: |
| |

Grey 1990 mm 49 mm 85 mm IP20





lightworks The details provided in this data sheet were prepared with due care but are still subject to error. We retain the right to make formal, technical and pricing changes. © 21/03/25 RIDI Lighting Ltd, Units 8 & 9 The Marshgate Centre, Harlow Business Park, Parkway, Harlow, Essex, CM19 5QP.

RIDI