iline 4

(+44 (0) 1279 450882

() WWW.RIDI-GROUP.CO.UK

- SALES@RIDI.CO.UK

Luminaire type

Product reference: Article Number: Product type: Mounting type: Applications:

IL4-WS-1972-830M-DADI-OP-FBES 97-IL400411ES Pendant Pendant Office, General and Retail

Specification text

Pendant luminaire from the iline 4 family. Symmetrical, Wide lighting distribution, UGR 22. Light output of 5997Im with an efficacy of 122Im/W. Light source colour temperature 3000KK and CRI 85. Complete with DALI control gear and self test $\rm \bar{3}hr$ emergency. Nominal dimensions L1972 x W40 x H62mm. Finished in Black.

> 5997 lm 122 lm/W 49.1W DALI 1-100% Yes 3000K K < 3 85



Lighting performance


Physical details

Finish:	
Length:	
Width:	
Height:	
IP Rating:	

Black 1972 mm 40 mm 62 mm IP20

Symmetrical Wide 22







RIDI

The details provided in this data sheet were prepared with due care but are still subject to error. We retain the right to make formal, technical and pricing changes. © 21/03/25 RIDI Lighting Ltd, Units 8 & 9 The Marshgate Centre, Harlow Business Park, Parkway, Harlow, Essex, CM19 5QP.