iline 4

(+44 (0) 1279 450882

() WWW.RIDI-GROUP.CO.UK

- SALES@RIDI.CO.UK

Luminaire type


Product reference:
Article Number:
Product type:
Mounting type:
Applications:

IL4-WS-1972-830M-DADI-OP-FGED 97-IL400412ED Pendant Pendant Office, General and Retail

Specification text

Pendant luminaire from the iline 4 family. Symmetrical, Wide lighting distribution, UGR 22. Light output of 5997lm with an efficacy of 122lm/W. Light source colour temperature 3000KK and CRI 85. Complete with DALI control gear and DALI test 3hr emergency. Nominal dimensions L1972 $x\,W40\,x$ H62mm. Finished in Grey.

> 5997 lm 122 lm/W 49.1 W DALI 1-100% Yes 3000K K < 3 85



Lighting performance

Output lumens:
Efficacy:
Rated power:
Control gear:
Dimming range:
DC Suitable:
Colour temperature:
MacAdams
CRI:
Radiation pattern:
Beam angle:
Unified glare rating (U.G.R):


Physical details

Finish:	
Length:	
Width:	
Height:	
IP Rating:	



Symmetrical Wide 22





lightworks

RIDI

The details provided in this data sheet were prepared with due care but are still subject to error. We retain the right to make formal, technical and pricing changes. © 21/03/25 RIDI Lighting Ltd, Units 8 & 9 The Marshgate Centre, Harlow Business Park, Parkway, Harlow, Essex, CM19 5QP.