

Luminaire type

| | |
|--------------------|-------------------------------|
| Product reference: | IL4-WS-1972-840M-DADI-OP-FBED |
| Article Number: | 97-IL400417ED |
| Product type: | Pendant |
| Mounting type: | Pendant |
| Applications: | Office, General and Retail |


Specification text

Pendant luminaire from the iline 4 family. Symmetrical, Wide lighting distribution, UGR 22. Light output of 6182lm with an efficacy of 126lm/W. Light source colour temperature 4000KK and CRI 85. Complete with DALI control gear and DALI test 3hr emergency. Nominal dimensions L1972 x W40 x H62mm. Finished in Black.



Lighting performance

| | |
|-------------------------------|-------------|
| Output lumens: | 6182 lm |
| Efficacy: | 126 lm/W |
| Rated power: | 49.1 W |
| Control gear: | DALI |
| Dimming range: | 1-100% |
| DC Suitable: | Yes |
| Colour temperature: | 4000K K |
| MacAdams | < 3 |
| CRI: | 85 |
| Radiation pattern: | Symmetrical |
| Beam angle: | Wide |
| Unified glare rating (U.G.R): | 22 |



Physical details

| | |
|------------|---------|
| Finish: | Black |
| Length: | 1972 mm |
| Width: | 40 mm |
| Height: | 62 mm |
| IP Rating: | IP20 |

