iline 4

- (+44 (0) 1279 450882
- () WWW.RIDI-GROUP.CO.UK

- SALES@RIDI.CO.UK

Luminaire type

Product reference:
Article Number:
Product type:
Mounting type:
Applications:

IL4-S-1972-830M-DAD-MP-FBED 97-IL400438ED Surface Mount Surface Office, General and Retail

Specification text

Surface Mount luminaire from the iline 4 family. Symmetrical, Wide lighting distribution, UGR 19. Light output of 3581Im with an efficacy of 105Im/W. Light source colour temperature 3000KK and CRI 85. Complete with DALI control gear and DALI test 3hr emergency. Nominal dimensions L1972 $x\,W40\,x$ H62mm. Finished in Black.

> 3581 lm 105 lm/W 34.1W DALI 1-100% Yes 3000K K < 3 85

Symmetrical Wide 19



Lighting performance


Output lumens:
Efficacy:
Rated power:
Control gear:
Dimming range:
DC Suitable:
Colour temperature:
MacAdams
CRI:
Radiation pattern:
Beam angle:
Unified glare rating (U.G.R):

Physical details

Finish:	
Length:	
Width:	
Height:	
IP Rating:	

Black 1972 mm 40 mm 62 mm IP20





lightworks

RIDI

The details provided in this data sheet were prepared with due care but are still subject to error. We retain the right to make formal, technical and pricing changes. © 21/03/25 RIDI Lighting Ltd, Units 8 & 9 The Marshgate Centre, Harlow Business Park, Parkway, Harlow, Essex, CM19 5QP.