# iline 4

( +44 (0) 1279 450882

WWW.RIDI-GROUP.CO.UK

- SALES@RIDI.CO.UK

### Luminaire type

Product reference:	IL4-S-1972-840M-DAD-MP-FWE
Article Number:	97-IL400443E
Product type:	Surface Mount
Mounting type:	Surface
Applications:	Office, General and Retail

#### **Specification text**

Surface Mount luminaire from the iline 4 family. Symmetrical, Wide lighting distribution, UGR 19. Light output of 3692lm with an efficacy of 108lm/W. Light source colour temperature 4000KK and CRI 85. Complete with DALI control gear and manual test 3hr emergency. Nominal dimensions L1972  ${\rm x}$ W40 x H62mm. Finished in White.

> 3692 lm 108 lm/W 34.1W DALI 1-100% Yes 4000K K < 3 85

Symmetrical Wide 19



### Lighting performance


Output lumens:		
Efficacy:		
Rated power:		
Control gear:		
Dimming range:		
DC Suitable:		
Colour temperature:		
MacAdams		
CRI:		
Radiation pattern:		
Beam angle:		
Unified glare rating (U.G.R):		

#### **Physical details**

Finish:	
Length:	
Width:	
Height:	
IP Rating:	

## White 1972 mm 40 mm 62 mm IP20





## lightworks

RIDI

The details provided in this data sheet were prepared with due care but are still subject to error. We retain the right to make formal, technical and pricing changes. © 21/03/25 RIDI Lighting Ltd, Units 8 & 9 The Marshgate Centre, Harlow Business Park, Parkway, Harlow, Essex, CM19 5QP.