iline 4

(+44 (0) 1279 450882

() WWW.RIDI-GROUP.CO.UK

- SALES@RIDI.CO.UK

Luminaire type

| Product reference: |
|--------------------|
| Article Number: |
| Product type: |
| Mounting type: |
| Applications: |

IL4-S-1972-830M-DAD-OP-FGES 97-IL400448ES Surface Mount Surface Office, General and Retail

Specification text

Surface Mount luminaire from the iline 4 family. Symmetrical, Wide lighting distribution, UGR 22. Light output of 4154Im with an efficacy of 122Im/W. Light source colour temperature 3000KK and CRI 85. Complete with DALI control gear and self test 3hr emergency. Nominal dimensions L1972 x W40 x H62mm. Finished in Grey.

> 4154 Im 122 lm/W 34.1W DALI 1-100% Yes 3000K K < 3 85

Symmetrical Wide 22



Lighting performance


| Output lumens: |
|-------------------------------|
| Efficacy: |
| Rated power: |
| Control gear: |
| Dimming range: |
| DC Suitable: |
| Colour temperature: |
| MacAdams |
| CRI: |
| Radiation pattern: |
| Beam angle: |
| Unified glare rating (U.G.R): |

Physical details

| Finish: | | |
|------------|--|--|
| Length: | | |
| Width: | | |
| Height: | | |
| IP Rating: | | |
| | | |

Grey 1972 mm 40 mm 62 mm IP20





lightworks

RIDI

The details provided in this data sheet were prepared with due care but are still subject to error. We retain the right to make formal, technical and pricing changes. © 21/03/25 RIDI Lighting Ltd, Units 8 & 9 The Marshgate Centre, Harlow Business Park, Parkway, Harlow, Essex, CM19 5QP.