# iline 4

( +44 (0) 1279 450882

() WWW.RIDI-GROUP.CO.UK

- SALES@RIDI.CO.UK

### Luminaire type

Product reference:	IL4-S-19
Article Number:	97-IL40
Product type:	Surface
Mounting type:	Surface
Applications:	Office, 0

972-840M-DAD-OP-FWES 0452ES e Mount General and Retail

#### **Specification text**

Surface Mount luminaire from the iline 4 family. Symmetrical, Wide lighting distribution, UGR 22. Light output of 4282lm with an efficacy of 126lm/W. Light source colour temperature 4000KK and CRI 85. Complete with DALI control gear and self test 3hr emergency. Nominal dimensions L1972 x W40 x  $\,$ H62mm. Finished in White.



## Lighting performance


Output lumens:	4282 lm
Efficacy:	126 lm/W
Rated power:	34.1W
Control gear:	DALI
Dimming range:	1-100%
DC Suitable:	Yes
Colour temperature:	4000K K
MacAdams	< 3
CRI:	85
Radiation pattern:	Symmetrical
Beam angle:	Wide
Unified glare rating (U.G.R):	22

#### **Physical details**

Finish:	
Length:	
Width:	
Height:	
IP Rating:	







# lightworks

RIDI

The details provided in this data sheet were prepared with due care but are still subject to error. We retain the right to make formal, technical and pricing changes. © 21/03/25 RIDI Lighting Ltd, Units 8 & 9 The Marshgate Centre, Harlow Business Park, Parkway, Harlow, Essex, CM19 5QP.