iline 4

(+44 (0) 1279 450882

() WWW.RIDI-GROUP.CO.UK

- SALES@RIDI.CO.UK

Luminaire type

Product reference:	IL6-R-1977-830M-DAD-MP-FWES
Article Number:	97-IL400520ES
Product type:	Recessed
Mounting type:	Recessed
Applications:	Office, General and Retail

Specification text

Recessed luminaire from the iline 4 family. Symmetrical, Wide lighting distribution, UGR 19. Light output of 3581lm with an efficacy of 105lm/W. Light source colour temperature 3000KK and CRI 85. Complete with DALI control gear and self test 3hr emergency. Nominal dimensions L1977 x W54 x H85mm. Finished in White.

> 3581 lm 105 lm/W 34.1W DALI 1-100% Yes 3000K K < 3 85

Symmetrical Wide 19

Lighting performance

Output lumens:	
Efficacy:	
Rated power:	
Control gear:	
Dimming range:	
DC Suitable:	
Colour temperature:	
MacAdams	
CRI:	
Radiation pattern:	
Beam angle:	
Unified glare rating (U.G.R):	

Physical details


Finish:	
Length:	
Width:	
Height:	
IP Rating:	

1977 mm 54 mm 85 mm IP20

White









RIDI

The details provided in this data sheet were prepared with due care but are still subject to error. We retain the right to make formal, technical and pricing changes. © 21/03/25 RIDI Lighting Ltd, Units 8 & 9 The Marshgate Centre, Harlow Business Park, Parkway, Harlow, Essex, CM19 5QP.