

Luminaire type

| | |
|--------------------|-----------------------------|
| Product reference: | IL6-R-1977-830M-DAD-MP-FBED |
| Article Number: | 97-IL400521ED |
| Product type: | Recessed |
| Mounting type: | Recessed |
| Applications: | Office, General and Retail |

Specification text

Recessed luminaire from the iline 4 family. Symmetrical, Wide lighting distribution, UGR 19. Light output of 3581lm with an efficacy of 105lm/W. Light source colour temperature 3000KK and CRI 85. Complete with DALI control gear and DALI test 3hr emergency. Nominal dimensions L1977 x W54 x H85mm. Finished in Black.

Lighting performance

| | |
|--------------------------------|-------------|
| Output lumens: | 3581 lm |
| Efficacy: | 105 lm/W |
| Rated power: | 34.1 W |
| Control gear: | DALI |
| Dimming range: | 1-100% |
| DC Suitable: | Yes |
| Colour temperature: | 3000K K |
| MacAdams | < 3 |
| CRI: | 85 |
| Radiation pattern: | Symmetrical |
| Beam angle: | Wide |
| Unified glare rating (U.G.R.): | 19 |

Physical details

| | |
|------------|---------|
| Finish: | Black |
| Length: | 1977 mm |
| Width: | 54 mm |
| Height: | 85 mm |
| IP Rating: | IP20 |

