# iline 4

( +44 (0) 1279 450882

() WWW.RIDI-GROUP.CO.UK

- SALES@RIDI.CO.UK

## Luminaire type

Product reference:
Article Number:
Product type:
Mounting type:
Applications:


IL6-R-1977-840M-DAD-MP-FBED 97-IL400524ED Recessed Recessed Office, General and Retail

### **Specification text**

Recessed luminaire from the iline 4 family. Symmetrical, Wide lighting distribution, UGR 19. Light output of 3692lm with an efficacy of 108lm/W. Light source colour temperature 4000KK and CRI 85. Complete with DALI control gear and DALI test 3hr emergency. Nominal dimensions L1977  $x\,W54\,x$ H85mm. Finished in Black.

> 3692 lm 108 lm/W 34.1W DALI 1-100% Yes 4000K K < 3 85

Symmetrical Wide 19



## Lighting performance

Output lumens:
Efficacy:
Rated power:
Control gear:
Dimming range:
DC Suitable:
Colour temperature:
MacAdams
CRI:
Radiation pattern:
Beam angle:
Unified glare rating (U.G.R):

#### **Physical details**

Finish:		
Length:		
Width:		
Height:		
IP Rating:		

## Black 1977 mm 54 mm 85 mm IP20





RIDI

The details provided in this data sheet were prepared with due care but are still subject to error. We retain the right to make formal, technical and pricing changes. © 21/03/25 RIDI Lighting Ltd, Units 8 & 9 The Marshgate Centre, Harlow Business Park, Parkway, Harlow, Essex, CM19 5QP.

