

## Luminaire type

|                    |                             |
|--------------------|-----------------------------|
| Product reference: | IL6-R-1977-840M-DAD-MP-FGES |
| Article Number:    | 97-IL400525ES               |
| Product type:      | Recessed                    |
| Mounting type:     | Recessed                    |
| Applications:      | Office, General and Retail  |

## Specification text

Recessed luminaire from the iline 4 family. Symmetrical, Wide lighting distribution, UGR 19. Light output of 3692lm with an efficacy of 108lm/W. Light source colour temperature 4000KK and CRI 85. Complete with DALI control gear and self test 3hr emergency. Nominal dimensions L1977 x W54 x H85mm. Finished in Grey.

## Lighting performance

|                                |             |
|--------------------------------|-------------|
| Output lumens:                 | 3692 lm     |
| Efficacy:                      | 108 lm/W    |
| Rated power:                   | 34.1 W      |
| Control gear:                  | DALI        |
| Dimming range:                 | 1-100%      |
| DC Suitable:                   | Yes         |
| Colour temperature:            | 4000K K     |
| MacAdams                       | < 3         |
| CRI:                           | 85          |
| Radiation pattern:             | Symmetrical |
| Beam angle:                    | Wide        |
| Unified glare rating (U.G.R.): | 19          |

## Physical details

|            |         |
|------------|---------|
| Finish:    | Grey    |
| Length:    | 1977 mm |
| Width:     | 54 mm   |
| Height:    | 85 mm   |
| IP Rating: | IP20    |

