# iline 4

( +44 (0) 1279 450882

() WWW.RIDI-GROUP.CO.UK

- SALES@RIDI.CO.UK

#### Luminaire type

Product reference:				
Article Number:				
Product type:				
Mounting type:				
Applications:				


IL6-R-1977-830M-DAD-OP-FGE 97-IL400528E Recessed Recessed Office, General and Retail

### **Specification text**

Recessed luminaire from the iline 4 family. Symmetrical, Wide lighting distribution, UGR 22. Light output of 4154lm with an efficacy of 122lm/W. Light source colour temperature 3000KK and CRI 85. Complete with DALI control gear and manual test 3hr emergency. Nominal dimensions L1977 x W54 xH85mm. Finished in Grey.

> 4154 lm 122 lm/W 34.1W DALI 1-100% Yes 3000K K < 3 85

Symmetrical Wide 22



## Lighting performance


Output lumens:
Efficacy:
Rated power:
Control gear:
Dimming range:
DC Suitable:
Colour temperature:
MacAdams
CRI:
Radiation pattern:
Beam angle:
Unified glare rating (U.G.R):

#### **Physical details**

Finish:		
Length:		
Width:		
Height:		
IP Rating:		







# lightworks

RIDI

The details provided in this data sheet were prepared with due care but are still subject to error. We retain the right to make formal, technical and pricing changes. © 21/03/25 RIDI Lighting Ltd, Units 8 & 9 The Marshgate Centre, Harlow Business Park, Parkway, Harlow, Essex, CM19 5QP.