# iline 5

+44(0)1279450882

WWW.RIDI-GROUP.CO.UK

SALES@RIDI.CO.UK

## Luminaire type

Product reference: Article Number: Product type: Mounting type: Applications: IL5-WS-1150-830M-DADI-MP-FBE 97-IL500002E Pendant Pendant Office, General and Retail

#### Specification text

Pendant luminaire from the iline 5 family. Symmetrical, Wide lighting distribution, UGR <19. Light output of 5481lm with an efficacy of 1111m/W. Light source colour temperature 3000KK and CRI 85. Complete with DALI control gear. Nominal dimensions L1150 x W49 x H85mm. Finished in Black.

> 5481 lm 111 lm/W 49.2 W DALI 1-100% Yes 3000K K < 3 85



## Lighting performance


Output lumens:
Efficacy:
Rated power:
Control gear:
Dimming range:
DC Suitable:
Colour temperature:
MacAdams
CRI:
Radiation pattern:
Beam angle:
Unified glare rating (U.G.R):


**Physical details** 

Finish:	
Length:	
Width:	
Height:	
IP Rating:	

# Black 1150 mm 49 mm 85 mm IP20

Symmetrical Wide <19







RIDI

The details provided in this data sheet were prepared with due care but are still subject to error. We retain the right to make formal, technical and pricing changes. © 21/03/25 RIDI Lighting Ltd, Units 8 & 9 The Marshgate Centre, Harlow Business Park, Parkway, Harlow, Essex, CM19 5QP.