

Luminaire type

| | |
|--------------------|----------------------------|
| Product reference: | IL5-S-1150-840M-DAD-OP-FB |
| Article Number: | 97-IL500053 |
| Product type: | Surface Mount |
| Mounting type: | Surface |
| Applications: | Office, General and Retail |

Specification text

Surface Mount luminaire from the iline 5 family. Symmetrical, Wide lighting distribution, UGR <22. Light output of 2678lm with an efficacy of 97lm/W. Light source colour temperature 4000KK and CRI 85. Complete with DALI control gear. Nominal dimensions L1150 x W49 x H85mm. Finished in Black.



Lighting performance

| | |
|-------------------------------|-------------|
| Output lumens: | 2678 lm |
| Efficacy: | 97 lm/W |
| Rated power: | 27.6 W |
| Control gear: | DALI |
| Dimming range: | 1-100% |
| DC Suitable: | Yes |
| Colour temperature: | 4000K K |
| MacAdams | < 3 |
| CRI: | 85 |
| Radiation pattern: | Symmetrical |
| Beam angle: | Wide |
| Unified glare rating (U.G.R): | <22 |



Physical details

| | |
|------------|---------|
| Finish: | Black |
| Length: | 1150 mm |
| Width: | 49 mm |
| Height: | 85 mm |
| IP Rating: | IP20 |

