# iline 5

+44 (0) 1279 450882

WWW.RIDI-GROUP.CO.UK

SALES@RIDI.CO.UK

#### Luminaire type

Product reference: Article Number: Product type: Mounting type: Applications: IL5-WS-1430-830M-DADI-OP-FWES 97-IL500210ES Pendant Pendant Office, General and Retail

### Specification text

Pendant luminaire from the iline 5 family. Symmetrical, Wide lighting distribution, UGR <22. Light output of 7706lm with an efficacy of 122lm/W. Light source colour temperature 3000KK and CRI 85. Complete with DALI control gear. Nominal dimensions L1430 x W49 x H85mm. Finished in White.

7706 lm 122 lm/W 63 W DALI 1-100% Yes 3000K K < 3 85



### Lighting performance


Output lumens:
Efficacy:
Rated power:
Control gear:
Dimming range:
DC Suitable:
Colour temperature:
MacAdams
CRI:
Radiation pattern:
Beam angle:
Unified glare rating (U.G.R):


#### **Physical details**

Finish:
Length:
Width:
Height:
IP Rating:

## White 1430 mm 49 mm 85 mm IP20

Symmetrical Wide <22





lightworks

RIDI

The details provided in this data sheet were prepared with due care but are still subject to error. We retain the right to make formal, technical and pricing changes. © 21/03/25 RIDI Lighting Ltd, Units 8 & 9 The Marshgate Centre, Harlow Business Park, Parkway, Harlow, Essex, CM19 5QP.