

Luminaire type

| | |
|--------------------|-------------------------------|
| Product reference: | IL5-WS-1430-830M-DADI-OP-FGED |
| Article Number: | 97-IL500212ED |
| Product type: | Pendant |
| Mounting type: | Pendant |
| Applications: | Office, General and Retail |

Specification text

Pendant luminaire from the iline 5 family. Symmetrical, Wide lighting distribution, UGR <22. Light output of 7706lm with an efficacy of 122lm/W. Light source colour temperature 3000K and CRI 85. Complete with DALI control gear. Nominal dimensions L1430 x W49 x H85mm. Finished in Grey.



Lighting performance

| | |
|--------------------------------|-------------|
| Output lumens: | 7706 lm |
| Efficacy: | 122 lm/W |
| Rated power: | 63 W |
| Control gear: | DALI |
| Dimming range: | 1-100% |
| DC Suitable: | Yes |
| Colour temperature: | 3000K K |
| MacAdams | < 3 |
| CRI: | 85 |
| Radiation pattern: | Symmetrical |
| Beam angle: | Wide |
| Unified glare rating (U.G.R.): | <22 |



Physical details

| | |
|------------|---------|
| Finish: | Grey |
| Length: | 1430 mm |
| Width: | 49 mm |
| Height: | 85 mm |
| IP Rating: | IP20 |

