iline 5

+44 (0) 1279 450882

WWW.RIDI-GROUP.CO.UK

SALES@RIDI.CO.UK

Luminaire type

Product reference: Article Number: Product type: Mounting type: Applications: IL5-WS-1430-830M-DAD-OP-FG 97-IL500230 Pendant Pendant Office, General and Retail

Specification text

Pendant luminaire from the iline 5 family. Symmetrical, Wide lighting distribution, UGR <22. Light output of 3230lm with an efficacy of 94lm/W. Light source colour temperature 3000KK and CRI 85. Complete with DALI control gear. Nominal dimensions L1430 x W49 x H85mm. Finished in Grey.




Lighting performance


Output lumens:	3230 lm
Efficacy:	94 lm/W
Rated power:	34.3 W
Control gear:	DALI
Dimming range:	1-100%
DC Suitable:	Yes
Colour temperature:	3000K K
MacAdams	< 3
CRI:	85
Radiation pattern:	Symmetrical
Beam angle:	Wide
Unified glare rating (U.G.R):	<22

Physical details

Finish:	
Length:	
Width:	
Height:	
IP Rating:	









RIDI

The details provided in this data sheet were prepared with due care but are still subject to error. We retain the right to make formal, technical and pricing changes. © 21/03/25 RIDI Lighting Ltd, Units 8 & 9 The Marshgate Centre, Harlow Business Park, Parkway, Harlow, Essex, CM19 5QP.