iline 5

+44(0)1279450882

WWW.RIDI-GROUP.CO.UK

SALES@RIDI.CO.UK

Luminaire type

Product reference:
Article Number:
Product type:
Mounting type:
Applications:

IL5-R-1440-830M-DAD-OP-FWES 97-IL500326ES Recessed Recessed Office, General and Retail

Specification text

Recessed luminaire from the iline 5 family. Symmetrical, Wide lighting distribution, UGR <22. Light output of 3230lm with an efficacy of 94lm/W. Light source colour temperature 3000KK and CRI 85. Complete with DALI control gear. Nominal dimensions L1445 x W60 x H80mm. Finished in White.



Lighting performance


Output lumens:	3230 lm
Efficacy:	94 lm/W
Rated power:	34.3 W
Control gear:	DALI
Dimming range:	1-100%
DC Suitable:	Yes
Colour temperature:	3000K K
MacAdams	< 3
CRI:	85
Radiation pattern:	Symmetrical
Beam angle:	Wide
Unified glare rating (U.G.R):	<22

Physical details

Finish:		
Length:		
Width:		
Height:		
IP Rating:		

White 1445 mm 60 mm 80 mm IP20





lightworks

RIDI

The details provided in this data sheet were prepared with due care but are still subject to error. We retain the right to make formal, technical and pricing changes. © 21/03/25 RIDI Lighting Ltd, Units 8 & 9 The Marshgate Centre, Harlow Business Park, Parkway, Harlow, Essex, CM19 5QP.