iline 5

+44(0)1279450882

WWW.RIDI-GROUP.CO.UK

SALES@RIDI.CO.UK

Luminaire type

Product reference: Article Number: Product type: Mounting type: Applications: IL5-R-1440-840M-DAD-OP-FB 97-IL500330 Recessed Recessed Office, General and Retail

Specification text

Recessed luminaire from the iline 5 family. Symmetrical, Wide lighting distribution, UGR <22. Light output of 3330lm with an efficacy of 97lm/W. Light source colour temperature 4000KK and CRI 85. Complete with DALI control gear. Nominal dimensions L1445 x W60 x H80mm. Finished in Black.

> 3330 lm 97 lm/W 34.3 W DALI 1-100% Yes 4000K K < 3 85



Lighting performance

Output lumens:
Efficacy:
Rated power:
Control gear:
Dimming range:
DC Suitable:
Colour temperature:
MacAdams
CRI:
Radiation pattern:
Beam angle:
Unified glare rating (U.G.R):


Physical details

Finish:		
Length:		
Width:		
Height:		
IP Rating:		

Black 1445 mm 60 mm 80 mm IP20

Symmetrical Wide <22





lightworks

RIDI

The details provided in this data sheet were prepared with due care but are still subject to error. We retain the right to make formal, technical and pricing changes. © 21/03/25 RIDI Lighting Ltd, Units 8 & 9 The Marshgate Centre, Harlow Business Park, Parkway, Harlow, Essex, CM19 5QP.