# iline 5

+44 (0) 1279 450882

WWW.RIDI-GROUP.CO.UK

SALES@RIDI.CO.UK

### Luminaire type

Product reference: Article Number: Product type: Mounting type: Applications: IL5-WS-1990-830M-DADI-MP-FGE 97-IL500403E Pendant Pendant Office, General and Retail

### Specification text

Pendant luminaire from the iline 5 family. Symmetrical, Wide lighting distribution, UGR <19. Light output of 10275Im with an efficacy of 113Im/W. Light source colour temperature 3000KK and CRI 85. Complete with DALI control gear. Nominal dimensions L1990 x W49 x H85mm. Finished in Grey.

10275 lm 113 lm/W 90.8 W DALI 1-100% Yes 3000K K < 3 85

Symmetrical Wide <19




### Lighting performance


Output lumens:	
Efficacy:	
Rated power:	
Control gear:	
Dimming range:	
DC Suitable:	
Colour temperature:	
MacAdams	
CRI:	
Radiation pattern:	
Beam angle:	
Unified glare rating (U.G.R):	

#### **Physical details**

Finish:	
Length:	
Width:	
Height:	
IP Rating:	

## Grey 1990 mm 49 mm 85 mm IP20







RIDI

The details provided in this data sheet were prepared with due care but are still subject to error. We retain the right to make formal, technical and pricing changes. © 21/03/25 RIDI Lighting Ltd, Units 8 & 9 The Marshgate Centre, Harlow Business Park, Parkway, Harlow, Essex, CM19 5QP.