iline 5

+44(0)1279450882

WWW.RIDI-GROUP.CO.UK

SALES@RIDI.CO.UK

Luminaire type

Product reference: Article Number: Product type: Mounting type: Applications: IL5-WS-1990-830M-DADI-OP-FBES 97-IL500411ES Pendant Pendant Office, General and Retail

Specification text

Pendant luminaire from the iline 5 family. Symmetrical, Wide lighting distribution, UGR <22. Light output of 11148lm with an efficacy of 123lm/W. Light source colour temperature 3000KK and CRI 85. Complete with DALI control gear. Nominal dimensions L1990 x W49 x H85mm. Finished in Black.

11148 lm 123 lm/W 90.8 W DALI 1-100% Yes 3000K K < 3 85



Lighting performance


Output lumens:
Efficacy:
Rated power:
Control gear:
Dimming range:
DC Suitable:
Colour temperature:
MacAdams
CRI:
Radiation pattern:
Beam angle:
Unified glare rating (U.G.R):


Physical details

Finish:
Length:
Width:
Height:
IP Rating:

Black 1990 mm 49 mm 85 mm IP20

Symmetrical Wide <22





lightworks

RIDI

The details provided in this data sheet were prepared with due care but are still subject to error. We retain the right to make formal, technical and pricing changes. © 21/03/25 RIDI Lighting Ltd, Units 8 & 9 The Marshgate Centre, Harlow Business Park, Parkway, Harlow, Essex, CM19 5QP.