

## Luminaire type

|                    |                             |
|--------------------|-----------------------------|
| Product reference: | IL5-WS-1990-830M-DAD-MP-FWE |
| Article Number:    | 97-IL500419E                |
| Product type:      | Pendant                     |
| Mounting type:     | Pendant                     |
| Applications:      | Office, General and Retail  |

## Specification text

Pendant luminaire from the iline 5 family. Symmetrical, Wide lighting distribution, UGR <19. Light output of 4398lm with an efficacy of 92lm/W. Light source colour temperature 3000K and CRI 85. Complete with DALI control gear. Nominal dimensions L1990 x W49 x H85mm. Finished in White.



## Lighting performance

|                                |             |
|--------------------------------|-------------|
| Output lumens:                 | 4398 lm     |
| Efficacy:                      | 92 lm/W     |
| Rated power:                   | 47.7 W      |
| Control gear:                  | DALI        |
| Dimming range:                 | 1-100%      |
| DC Suitable:                   | Yes         |
| Colour temperature:            | 3000K       |
| MacAdams                       | < 3         |
| CRI:                           | 85          |
| Radiation pattern:             | Symmetrical |
| Beam angle:                    | Wide        |
| Unified glare rating (U.G.R.): | <19         |



## Physical details

|            |         |
|------------|---------|
| Finish:    | White   |
| Length:    | 1990 mm |
| Width:     | 49 mm   |
| Height:    | 85 mm   |
| IP Rating: | IP20    |

