iline 5

+44 (0) 1279 450882

WWW.RIDI-GROUP.CO.UK

SALES@RIDI.CO.UK

Luminaire type

Product reference: Article Number: Product type: Mounting type: Applications: IL5-WS-1990-840M-DAD-MP-FBES 97-IL500426ES Pendant Pendant Office, General and Retail

Specification text

Pendant luminaire from the iline 5 family. Symmetrical, Wide lighting distribution, UGR <19. Light output of 4534lm with an efficacy of 95lm/W. Light source colour temperature 4000KK and CRI 85. Complete with DALI control gear. Nominal dimensions L1990 x W49 x H85mm. Finished in Black.

4534 lm 95 lm/W 47.7 W DALI 1-100% Yes 4000K K < 3 85



Lighting performance


Output lumens:	
Efficacy:	
Rated power:	
Control gear:	
Dimming range:	
DC Suitable:	
Colour temperature:	
MacAdams	
CRI:	
Radiation pattern:	
Beam angle:	
Unified glare rating (U.G.R):	


Physical details

Finish:	
Length:	
Width:	
Height:	
IP Rating:	

Black 1990 mm 49 mm 85 mm IP20

Symmetrical Wide <19







RIDI

The details provided in this data sheet were prepared with due care but are still subject to error. We retain the right to make formal, technical and pricing changes. © 21/03/25 RIDI Lighting Ltd, Units 8 & 9 The Marshgate Centre, Harlow Business Park, Parkway, Harlow, Essex, CM19 5QP.