# iline 5

+44 (0) 1279 450882

WWW.RIDI-GROUP.CO.UK

SALES@RIDI.CO.UK

### Luminaire type

| Product reference: |
|--------------------|
| Article Number:    |
| Product type:      |
| Mounting type:     |
| Applications:      |

IL5-S-1990-830M-DAD-MP-FBED 97-IL500438ED Surface Mount Surface Office, General and Retail

## Specification text

Surface Mount luminaire from the iline 5 family. Symmetrical, Wide lighting distribution, UGR <19. Light output of 4398Im with an efficacy of 92Im/W. Light source colour temperature 3000KK and CRI 85. Complete with DALI control gear. Nominal dimensions L1990 x W49 x H85mm. Finished in Black.

4398 lm 92 lm/W 47.7 W DALI 1-100% Yes 3000K K < 3 85

Symmetrical Wide <19



# Lighting performance


| Output lumens:                |
|-------------------------------|
| Efficacy:                     |
| Rated power:                  |
| Control gear:                 |
| Dimming range:                |
| DC Suitable:                  |
| Colour temperature:           |
| MacAdams                      |
| CRI:                          |
| Radiation pattern:            |
| Beam angle:                   |
| Unified glare rating (U.G.R): |

#### **Physical details**

| Finish:    |
|------------|
| Length:    |
| Width:     |
| Height:    |
| IP Rating: |
|            |

# Black 1990 mm 49 mm 85 mm IP20





lightworks

RIDI

The details provided in this data sheet were prepared with due care but are still subject to error. We retain the right to make formal, technical and pricing changes. © 21/03/25 RIDI Lighting Ltd, Units 8 & 9 The Marshgate Centre, Harlow Business Park, Parkway, Harlow, Essex, CM19 5QP.