iline 5

+44 (0) 1279 450882

WWW.RIDI-GROUP.CO.UK

SALES@RIDI.CO.UK

Luminaire type

| Product reference: |
|--------------------|
| Article Number: |
| Product type: |
| Mounting type: |
| Applications: |

IL5-S-1990-830M-DAD-MP-FGE 97-IL500439E Surface Mount Surface Office, General and Retail

Specification text

Surface Mount luminaire from the iline 5 family. Symmetrical, Wide lighting distribution, UGR <19. Light output of 4398lm with an efficacy of 92lm/W. Light source colour temperature 3000KK and CRI 85. Complete with DALI control gear. Nominal dimensions L1990 x W49 x H85mm. Finished in Grey.

4398 lm 92 lm/W 47.7 W DALI 1-100% Yes 3000K K < 3 85



Lighting performance

| Output lumens: |
|-------------------------------|
| Efficacy: |
| Rated power: |
| Control gear: |
| Dimming range: |
| DC Suitable: |
| Colour temperature: |
| MacAdams |
| CRI: |
| Radiation pattern: |
| Beam angle: |
| Unified glare rating (U.G.R): |


Physical details

| Finish: | |
|------------|--|
| Length: | |
| Width: | |
| Height: | |
| IP Rating: | |
| | |



Symmetrical Wide <19





lightworks

RIDI

The details provided in this data sheet were prepared with due care but are still subject to error. We retain the right to make formal, technical and pricing changes. © 21/03/25 RIDI Lighting Ltd, Units 8 & 9 The Marshgate Centre, Harlow Business Park, Parkway, Harlow, Essex, CM19 5QP.