iline 5

+44(0)1279450882

WWW.RIDI-GROUP.CO.UK

SALES@RIDI.CO.UK

Luminaire type

Product reference:
Article Number:
Product type:
Mounting type:
Applications:

IL5-S-1990-840M-DAD-OP-FGES 97-IL500454ES Surface Mount Surface Office, General and Retail

Specification text

Surface Mount luminaire from the iline 5 family. Symmetrical, Wide lighting distribution, UGR <22. Light output of 4634Im with an efficacy of 97Im/W. Light source colour temperature 4000KK and CRI 85. Complete with DALI control gear. Nominal dimensions L1990 x W49 x H85mm. Finished in Grey.



Lighting performance


Output lumens:	4634 lm
Efficacy:	97 lm/W
Rated power:	47.7 W
Control gear:	DALI
Dimming range:	1-100%
DC Suitable:	Yes
Colour temperature:	4000K K
MacAdams	< 3
CRI:	85
Radiation pattern:	Symmetrical
Beam angle:	Wide
Unified glare rating (U.G.R):	<22

Physical details

Finish:	
Length:	
Width:	
Height:	
IP Rating:	

Grey 1990 mm 49 mm 85 mm IP20





lightworks

RIDI

The details provided in this data sheet were prepared with due care but are still subject to error. We retain the right to make formal, technical and pricing changes. © 21/03/25 RIDI Lighting Ltd, Units 8 & 9 The Marshgate Centre, Harlow Business Park, Parkway, Harlow, Essex, CM19 5QP.