iline 5

+44 (0) 1279 450882

WWW.RIDI-GROUP.CO.UK

SALES@RIDI.CO.UK

Luminaire type

Product reference: Article Number: Product type: Mounting type: Applications: IL5-R-2000-830M-DAD-OP-FGE 97-IL500528E Recessed Recessed Office, General and Retail

Specification text

Recessed luminaire from the iline 5 family. Symmetrical, Wide lighting distribution, UGR <22. Light output of 4495lm with an efficacy of 94lm/W. Light source colour temperature 3000KK and CRI 85. Complete with DALI control gear. Nominal dimensions L2005 x W60 x H80mm. Finished in Grey.

> 4495 lm 94 lm/W 47.7 W DALI 1-100% Yes 3000K K < 3 85

Symmetrical Wide <22




Lighting performance

Output lumens:	
Efficacy:	
Rated power:	
Control gear:	
Dimming range:	
DC Suitable:	
Colour temperature:	
MacAdams	
CRI:	
Radiation pattern:	
Beam angle:	
Unified glare rating (U.G.R):	

Physical details

Finish:	Grey
Length:	2005 mm
Width:	60 mm
Height:	80 mm
IP Rating:	IP20





lightworks

RIDI

The details provided in this data sheet were prepared with due care but are still subject to error. We retain the right to make formal, technical and pricing changes. © 21/03/25 RIDI Lighting Ltd, Units 8 & 9 The Marshgate Centre, Harlow Business Park, Parkway, Harlow, Essex, CM19 5QP.