iline 6

+44 (0) 1279 450882

WWW.RIDI-GROUP.CO.UK

SALES@RIDI.CO.UK

Luminaire type

Product reference: Article Number: Product type: Mounting type: Applications: IL6-WS-1198-830M-DADI-OP-FBE 97-IL600011E Pendant Pendant Office, General and Retail

Specification text

Pendant luminaire from the iline 6 family. Symmetrical, Wide lighting distribution, UGR <22. Light output of 3821.8lm with an efficacy of 132lm/W. Light source colour temperature 3000K and CRI 85. Complete with DALI control gear and manual test 3hr emergency. Nominal dimensions L1198 x W60 x H80mm. Finished in Black.




Lighting performance


Output lumens:	3821.8 lm
Efficacy:	132 lm/W
Rated power:	29 W
Control gear:	DALI
Dimming range:	1-100%
DC Suitable:	Yes
Colour temperature:	3000 K
MacAdams	< 3
CRI:	85
Radiation pattern:	Symmetrical
Beam angle:	Wide
Unified glare rating (U.G.R):	<22

Physical details

Finish:		
Length:		
Width:		
Height:		
IP Rating:		



Black 1198 mm 60 mm 80 mm IP20





RIDI

The details provided in this data sheet were prepared with due care but are still subject to error. We retain the right to make formal, technical and pricing changes. © 21/03/25 RIDI Lighting Ltd, Units 8 & 9 The Marshgate Centre, Harlow Business Park, Parkway, Harlow, Essex, CM19 5QP.