# iline 6

+44 (0) 1279 450882

WWW.RIDI-GROUP.CO.UK

SALES@RIDI.CO.UK

## Luminaire type

Product reference:	П
Article Number:	9
Product type:	F
Mounting type:	F
Applications:	C

L6-R-1214-840M-DAD-MP-FWES 97-IL600123ES Recessed Recessed Office, General and Retail

#### **Specification text**

Recessed luminaire from the iline 6 family. Symmetrical, Wide lighting distribution, UGR <19. Light output of 2460lm with an efficacy of 117lm/W. Light source colour temperature 4000K and CRI 85. Complete with DALI control gear and self test 3hr emergency. Nominal dimensions L1214 x W76 x H76.5mm. Finished in White.



### Lighting performance

Output lumens:	2460 lm
Efficacy:	117 lm/W
Rated power:	0 W 0
Control gear:	DALI
Dimming range:	1-100%
DC Suitable:	Yes
Colour temperature:	4000 K
MacAdams	< 3
CRI:	85
Radiation pattern:	Symmetrical
Beam angle:	Wide
Unified glare rating (U.G.R):	<19

#### **Physical details**

Finish:		
Length:		
Width:		
Height:		
IP Rating:		







RIDI

The details provided in this data sheet were prepared with due care but are still subject to error. We retain the right to make formal, technical and pricing changes. © 21/03/25 RIDI Lighting Ltd, Units 8 & 9 The Marshgate Centre, Harlow Business Park, Parkway, Harlow, Essex, CM19 5QP.

