

Luminaire type

| | |
|--------------------|-------------------------------|
| Product reference: | IL6-WS-1478-830M-DADI-MP-FGES |
| Article Number: | 97-IL600203ES |
| Product type: | Pendant |
| Mounting type: | Pendant |
| Applications: | Office, General and Retail |

Specification text

Pendant luminaire from the iline 6 family. Symmetrical, Wide lighting distribution, UGR <19. Light output of 4559lm with an efficacy of 125lm/W. Light source colour temperature 3000K and CRI 85. Complete with DALI control gear and self test 3hr emergency. Nominal dimensions L1478 x W60 x H80mm. Finished in Grey.

Lighting performance

| | |
|--------------------------------|-------------|
| Output lumens: | 4559 lm |
| Efficacy: | 125 lm/W |
| Rated power: | 46.5 W |
| Control gear: | DALI |
| Dimming range: | 1-100% |
| DC Suitable: | Yes |
| Colour temperature: | 3000 K |
| MacAdams | < 3 |
| CRI: | 85 |
| Radiation pattern: | Symmetrical |
| Beam angle: | Wide |
| Unified glare rating (U.G.R.): | <19 |

Physical details

| | |
|------------|---------|
| Finish: | Grey |
| Length: | 1478 mm |
| Width: | 60 mm |
| Height: | 80 mm |
| IP Rating: | IP20 |

