# iline 6

+44 (0) 1279 450882

WWW.RIDI-GROUP.CO.UK

SALES@RIDI.CO.UK

## Luminaire type


Product reference: Article Number: Product type: Mounting type: Applications: IL6-WS-1478-840M-DADI-MP-FB 97-IL600208 Pendant Pendant Office, General and Retail

### **Specification text**

Pendant luminaire from the iline 6 family. Symmetrical, Wide lighting distribution, UGR <19. Light output of 4700lm with an efficacy of 129lm/W. Light source colour temperature 4000K and CRI 85. Complete with DALI control gear. Nominal dimensions L1478 x W60 x H80mm. Finished in Black.

4700 lm 129 lm/W 46.5 W DALI 1-100% Yes 4000 K < 3 85

Symmetrical Wide <19




## Lighting performance


Output lumens:
Efficacy:
Rated power:
Control gear:
Dimming range:
DC Suitable:
Colour temperature:
MacAdams
CRI:
Radiation pattern:
Beam angle:
Unified glare rating (U.G.R):

#### **Physical details**

Finish:	
Length:	
Width:	
Height:	
IP Rating:	







lightworks

RIDI

The details provided in this data sheet were prepared with due care but are still subject to error. We retain the right to make formal, technical and pricing changes. © 21/03/25 RIDI Lighting Ltd, Units 8 & 9 The Marshgate Centre, Harlow Business Park, Parkway, Harlow, Essex, CM19 5QP.