iline 6

+44 (0) 1279 450882

WWW.RIDI-GROUP.CO.UK

SALES@RIDI.CO.UK

Luminaire type

Product reference: Article Number: Product type: Mounting type: Applications: IL6-WS-1478-830M-DAD-MP-FG 97-IL600221 Pendant Pendant Office, General and Retail

Specification text

Pendant luminaire from the iline 6 family. Symmetrical, Wide lighting distribution, UGR <19. Light output of 2947.83Im with an efficacy of 113Im/W. Light source colour temperature 3000K and CRI 85. Complete with DALI control gear. Nominal dimensions L1478 x W60 x H80mm. Finished in Grey.

2947.83 lm 113 lm/W 23 W DALI 1-100% Yes 3000 K < 3 85

Symmetrical Wide <19




Lighting performance


Output lumens:
Efficacy:
Rated power:
Control gear:
Dimming range:
DC Suitable:
Colour temperature:
MacAdams
CRI:
Radiation pattern:
Beam angle:
Unified glare rating (U.G.R):

Physical details

Finish:		
Length:		
Width:		
Height:		
IP Rating:		







lightworks

RIDI

The details provided in this data sheet were prepared with due care but are still subject to error. We retain the right to make formal, technical and pricing changes. © 21/03/25 RIDI Lighting Ltd, Units 8 & 9 The Marshgate Centre, Harlow Business Park, Parkway, Harlow, Essex, CM19 5QP.