

## Luminaire type

|                    |                             |
|--------------------|-----------------------------|
| Product reference: | IL6-WS-1478-830M-DAD-OP-FWE |
| Article Number:    | 97-IL600228E                |
| Product type:      | Pendant                     |
| Mounting type:     | Pendant                     |
| Applications:      | Office, General and Retail  |

## Specification text

Pendant luminaire from the iline 6 family. Symmetrical, Wide lighting distribution, UGR <22. Light output of 3199.06lm with an efficacy of 123lm/W. Light source colour temperature 3000K and CRI 85. Complete with DALI control gear and manual test 3hr emergency. Nominal dimensions L1478 x W60 x H80mm. Finished in White.



## Lighting performance

|                                |             |
|--------------------------------|-------------|
| Output lumens:                 | 3199.06 lm  |
| Efficacy:                      | 123 lm/W    |
| Rated power:                   | 23 W        |
| Control gear:                  | DALI        |
| Dimming range:                 | 1-100%      |
| DC Suitable:                   | Yes         |
| Colour temperature:            | 3000 K      |
| MacAdams                       | < 3         |
| CRI:                           | 85          |
| Radiation pattern:             | Symmetrical |
| Beam angle:                    | Wide        |
| Unified glare rating (U.G.R.): | <22         |



## Physical details

|            |         |
|------------|---------|
| Finish:    | White   |
| Length:    | 1478 mm |
| Width:     | 60 mm   |
| Height:    | 80 mm   |
| IP Rating: | IP20    |

